TESS™ 600 ORDER FORM

YOUR DETAILS														DELIVERY DETAILS (Standard lead time 4-6 weeks)			
Compar	у				Contact							Required delivery date					
Email					Phone								ery address				
Address	;				Order no.												
				Quote no.				Delivery optio			ry options						
						Project						С	ustomer to collec	t (ExWorks)	GD to deliver (DAP – surcharge)		
		SYSTEM DIMENSIONS (MAX AREA 13.5m ²)				im²)	MOT	OR SIDE	E HEADBOX		NG Headbox fixing						
POS	QTY	QTY WIDTH (SW) DRAW (SD) max 3000 mm max 4500 m				RIGHT	DIRECT	BAC	К					Motor left			
1																	
2												Direct Back					Motor
3																	right
4												ORIENTATION		System draw (SD)		ġ	
5												Vertical					
6												Horizontal		aw (S	Syste	m width (SW)	
7												100171011					
8												LOCATION					Syste
9 10												Internal External*					System draw (SD)
10												*Only if protected					aw (S
12				_								under eaves.					
TOTAL												No wind classification, no warranty.			8,		*2 V
	POWDER COATING OPTIONS			MOTOR MAKE TYPE										HE/	M BAR FINISHES		
REF				All radio transmitters below are battery powered													
	R	RAL 9016 30% (traffic white matt = standard)			Sc	omfy Har	d Wired	Somfy Radi	Somfy Radio		Nice Hard Wired Nice		Radio		HIF!		
3075	С				SOM	SOMFY RADIO TRANSMITTERS				EF NICE RADIO TRANSMITTERS			QTY		Hem bar		
	·	RAL GLOSS LEVEL			7349	1 chan	d)		77	742 1 channel (hand held)				o V .	Hem bar		
20/7			30%	70% satin	90% gloss	7350	4+1 ch	annel (hand	held)	ld)	77	768 6 channel (hand l	neld)				
3067			matt			7351	16 channel (hand hel		eld)		77	743 1 channel (wall mounted)					1
						7352	1 chan	1 channel (wall mounted)			77	70 6 channel (wall mounted)				Hem bar end	d cap Sealant strip
MOTOR VOLTAGE OPTIONS					ACCESSORIES									Blac	ck sealant strip		
REF	REF				REF	EF							Whi	White sealant strip			
	Standard motor voltage: 230V AC/50 Hz			3522	2 Hirschmann plug							Blac	Black hem bar end cap				
	S	Special motor voltage: 110V AC/60 Hz				7774	Control unit TTU (to be able to set limits of Nice hardwired motor)							Whi	te hem bar end	d cap	
3079		Special motor voltage: 24V DC (24V DC motors incur a surcharge)				FORM COMPLETED BY											

SIGNATURE

PRINT NAME

TD31 TESS™ 600 order form May 2020

DATE

REGISTERED INSTALLER

TESS™ 600 FABRIC ORDER FORM

FABRIC ALWAYS SUPPLIED AND FITTED BY GUTHRIE DOUGLAS					
Fabric type					
Colour code*					
	uthrie Douglas approved fabrics colour chart				

www.guthriedouglas.com/fabric-choices

PLEASE SPECIFY WHERE YOU WOULD LIKE THE FABRIC FRONT AND BACK (SEE GD WEBSITE FOR MORE DETAILS)

	Flat side (FS)					
Fabric front	or					
	Head box side (HBS)					
PLEASE SPECIFY WHERE YOU WOULD LIKE THE POCKET WELDS TO BE (WELDS WILL BE VISIBLE)						
	Flat side (FS)					
Pocket weld	or					
	Head box side (HBS)					
 PLEASE NOTE Once ordered the fabric cannot be turned over. On blackout fabric, slight wrinkling has to be expected along the side guides. 						

· Depending on the system width mid welds may be present parallel to the head box.

• The position of the welds or their orientation cannot be guaranteed.

FABRIC	
Colour	
Coloui	

Fabric pocket flat side (FS)



Head box side (HBS)

Fabric pocket head box side (HBS)