

YOUR [	DETAI	LS											DELIVI	ERY DETAILS (	Standard lead	time 4-6 weeks)	
Company								Contact						ed delivery date			
Email								Phone					Deliver	y address			
Address	5							Order no.									
								Quote no.					Deliver	y options			
								Project					Cu	stomer to collec	t (ExWorks)	GD to deliver (DAP - surcharge	
	SYSTEM DIMENSIONS (MAX AREA 13.5				5m²) MOT		OR SIDE	DE RETURN P		(			Return Pulle	n Pulley Fixing			
POS	QTY	Y WIDTH (SW) DRAW (SD) (max 3000 mm) (max 4500 mm)				LEFT RIGHT		TOP	BACI	<					→ <b>——</b>		
1												10					
2														*	0	Back	
3												Top					
4													,				
5															M	otor	
6												•	Sys	tem width (SW)	<b></b>	left	
7												ORIENTATION			<b>■</b>		
8												Vertical			Syst	Moto	
9												Horizontal			System draw (SD)	righ	
10															raw (		
11												LOCATION					
12												Internal			₩ *		
TOTAL												External					
POWDER COATING OPTIONS				MOTOR MAKE TYPE									HE	M BAR FINISHES			
REF							А	II radio transmitt	ers be	low are	battery powered						
	F	RAL 9016 30% (traffic white matt = standard)		Somfy Hard Wired Somfy Radio				N	ce Hard Wired Nice	Radio	Hem	Hem bar end cap					
3075		Other RAL, sp	pecify belo	ow (surcha	arge)	REF	SOMF	Y RADIO TR	ANSMITTERS	QTY	REF	NICE RADIO TRANSMI	TTERS	QTY			
		RAL GLOSS LEVEL			7349	1 chann	1 channel (hand held)			7742	1 channel (hand held)				Hembar		
			30%	70%	90%	7350	4+1 cha	annel (hand l	neld)		7768					odr /	
3067			matt	satin	gloss	7351					7743	1 channel (wall mounted)					
						7352	1 chann	channel (wall mounted)			7770	6 channel (wall mounted)	(wall mounted)		Sealant strip		
<u> </u>	MOTOR VOLTAGE OPTIONS				ACCESSORIES								Bla	Black sealant strip			
REF	REF											White sealant strip					
	Standard motor voltage: 230V AC/50 Hz				3522 Hirschmann plug								Black hem bar end cap				
	Special motor voltage: 230 V /C/30 Hz				7774 Control unit TTU (to be able to set limits of Nice hardwired motor)								White hem bar end cap				
3079															<u> </u>		
	C	(24V DC motors incur a surcharge)				FORM	FORM COMPLETED BY							RECISTEDE	D INSTALLER	DATE	

FABRIC ALWAYS SUPPLIED AND FITTED BY GUTHRIE DOUGLAS						
Fabric type						
Colour code*						
*Please refer to the Guthrie Douglas approved fabrics colour chart www.guthriedouglas.com/fabric-choices						

PLEASE SPECIFY WHERE YOU WOULD LIKE THE FABRIC FRONT AND BACK (SEE GD WEBSITE FOR MORE DETAILS)							
	Flat side (FS)						
Fabric front	or						
	Head box side (HBS)						
PLEASE SPECIFY WHERE YOU WOULD LIKE THE POCKET WELDS TO BE (WELDS WILL BE VISIBLE)							
	Flat side (FS)						
Pocket weld	or						
	Head box side (HBS)						

## PLEASE NOTE

- · Once ordered the fabric cannot be turned over.
- On blackout fabric, slight wrinkling has to be expected along the side guides.
- Depending on the system width mid welds may be present parallel to the head box.
- The position of the welds or their orientation cannot be guaranteed.



Fabric pocket flat side (FS)

FABRIC

Colour



Head box side (HBS)

Fabric pocket head box side (HBS)