

# TESS™ 660 RECESS FIX ORDER FORM

| YOUR DETAILS |  |           |  | DELIVERY DETAILS (Standard lead time 4-6 weeks) |                               |                                 |  |
|--------------|--|-----------|--|---|-------------------------------|---------------------------------|--|
| Company      |  | Contact   |  | Required delivery date                          |                               |                                 |  |
| Email        |  | Phone     |  | Delivery address                                |                               |                                 |  |
| Address      |  | Order no. |  | Delivery options                                |                               |                                 |  |
|              |  | Quote no. |  |   | Customer to collect (ExWorks) | GD to deliver (DAP - surcharge) |  |
|              |  | Project   |  |   |                               |                                 |  |

| POS | QTY | REVEAL DIMENSIONS (REFER TO DATASHEET) |                     | MOTOR SIDE |       | SYSTEM TYPE |     | LID (SINGLE SCREEN) |    |
|-----|-----|--|---------------------|------------|-------|-------------|-----|---------------------|----|
|     |     | WIDTH (RW)<br>max 3000 mm              | DRAW<br>max 3000 mm | LEFT       | RIGHT | SINGLE      | DUO | YES                 | NO |
| 1   |     |  |                     |            |       |             |     |                     |    |
| 2   |     |  |                     |            |       |             |     |                     |    |
| 3   |     |  |                     |            |       |             |     |                     |    |
| 4   |     |  |                     |            |       |             |     |                     |    |
| 5   |     |  |                     |            |       |             |     |                     |    |
| 6   |     |  |                     |            |       |             |     |                     |    |
| 7   |     |  |                     |            |       |             |     |                     |    |
| 8   |     |  |                     |            |       |             |     |                     |    |
| 9   |     |  |                     |            |       |             |     |                     |    |
| 10  |     |  |                     |            |       |             |     |                     |    |

**PLEASE BE ADVISED**  
We recommend the use of radio motors with twin head box configurations and overhead installations to avoid the need for relays and to aid with commissioning.

**IMPORTANT**  
The TESS™660 RECESS FIX system width can be adjusted and increased by up to 18mm however the system width cannot be reduced and made narrower.  
  
We therefore recommend measuring the recess width (RW) at least 3 points ideally using a laser distance gauge.  
  
Specify the smallest recess width (RW) when placing an order. Check that the difference between the smallest and largest width does not exceed 18mm.  
  
The widths should be parallel, the draws should be parallel, and the diagonals (D) should be equal.

**ORIENTATION**  
Vertical  
Horizontal

**LOCATION**  
Internal  
External\*\*

\*\* Running direction only vertically or sloping from top to bottom: 15° minimum angle

**Single screen system**

**Duo screen system**

**Application area**

System dimensions

For duo screen system please specify if you wish for the motors to be on the same side

TOTAL

| POWDER COATING OPTIONS |  |             |                  |           |
|------------------------|--|-------------|------------------|-----------|
| REF                    |  |             |                  |           |
|                        | RAL 9016 30% (traffic white matt = standard) |             | Somfy Hard Wired |           |
| 3075                   | Other RAL, specify below (surcharge)         |             |                  |           |
| 3067                   | RAL  | GLOSS LEVEL |                  |           |
|                        |  | 30% matt    | 70% satin        | 90% gloss |

| MOTOR MAKE TYPE                                  |     |                          |  |
|--|-----|--------------------------|--|
| All radio transmitters below are battery powered |     |                          |  |
|  |     | Somfy Radio              |  |
| REF  | QTY |                          |  |
| 7349   |     | 1 channel (hand held)    |  |
| 7350   |     | 4+1 channel (hand held)  |  |
| 7351   |     | 16 channel (hand held)   |  |
| 7352   |     | 1 channel (wall mounted) |  |

| HEMBAR FINISHING OPTIONS |
|--------------------------|
|                          |
| Black sealant strip      |
| White sealant strip      |
| Black hem bar end cap    |
| White hem bar end cap    |

| MOTOR VOLTAGE OPTIONS |   |  |  |  |
|-----------------------|---|--|--|--|
| REF                   |   |  |  |  |
|                       | Standard motor voltage: 230V AC/50 Hz                           |  |  |  |
|                       | Special motor voltage: 110V AC/60 Hz                            |  |  |  |
| 3079                  | Special motor voltage: 24V DC (24V DC motors incur a surcharge) |  |  |  |

| ACCESSORIES |   |  |  |
|-------------|---|--|--|
| REF         |   |  |  |
| 3522        | Hirschmann plug   |  |  |
| 7774        | Control unit TTU (to be able to set limits of Nice hardwired motor) |  |  |

FORM COMPLETED BY ..... PRINT NAME ..... SIGNATURE ..... REGISTERED INSTALLER ..... DATE .....

# TESS™ 660 RECESS FIX FABRIC ORDER FORM

## SINGLE SCREEN SYSTEM

| FABRIC ALWAYS SUPPLIED AND FITTED BY GUTHRIE DOUGLAS  |                     |
|---|---------------------|
| Fabric type   |                     |
| Colour code*  |                     |
| *Please refer to the Guthrie Douglas approved fabrics colour chart<br>www.guthriedouglas.com/fabric-choices   |                     |
| PLEASE SPECIFY WHERE YOU WOULD LIKE THE FABRIC FRONT AND BACK<br>(SEE GD WEBSITE FOR MORE DETAILS)  |                     |
| Fabric front  | Flat side (FS)      |
|   | Head box side (HBS) |
| PLEASE SPECIFY WHERE YOU WOULD LIKE THE POCKET WELDS TO BE<br>(WELDS WILL BE VISIBLE)   |                     |
| Pocket weld   | Flat side (FS)      |
|   | Head box side (HBS) |
| <b>PLEASE NOTE</b> <ul style="list-style-type: none"> <li>• Once ordered the fabric cannot be turned over.</li> <li>• On blackout fabric, slight wrinkling has to be expected along the side guides.</li> <li>• Depending on the system width mid welds may be present parallel to the head box.</li> <li>• The position of the welds or their orientation cannot be guaranteed.</li> </ul> |                     |

## DUO SCREEN SYSTEM

| FABRIC ALWAYS SUPPLIED AND FITTED BY GUTHRIE DOUGLAS  |          |                       |          |
|---|----------|-----------------------|----------|
| Fabric type system 1  |          | Fabric type system 2  |          |
| Colour code system 1*   |          | Colour code system 2* |          |
| *Please refer to the Guthrie Douglas approved fabrics colour chart<br>www.guthriedouglas.com/fabric-choices   |          |                       |          |
| PLEASE SPECIFY WHERE YOU WOULD LIKE THE FABRIC FRONT AND BACK<br>(SEE GD WEBSITE FOR MORE DETAILS)  |          |                       |          |
| Fabric front System 1   | Outwards | Fabric front System 2 | Outwards |
|   | Inwards  |                       | Inwards  |
| PLEASE SPECIFY WHERE YOU WOULD LIKE THE POCKET WELDS TO BE<br>(WELDS WILL BE VISIBLE)   |          |                       |          |
| Pocket weld System 1  | Outwards | Pocket weld System 2  | Outwards |
|   | Inwards  |                       | Inwards  |
| <b>PLEASE NOTE</b> <ul style="list-style-type: none"> <li>• Once ordered the fabric cannot be turned over.</li> <li>• On blackout fabric, slight wrinkling has to be expected along the side guides.</li> <li>• Depending on the system width mid welds may be present parallel to the head box.</li> <li>• The position of the welds or their orientation cannot be guaranteed.</li> </ul> |          |                       |          |

